

Technical Information

Lessoflex BG6669

<u>Name</u>	Modified glutin jelly	
<u>Application</u>	<u>Papper converting or laminating</u>	
Physics property	Boxes making and paper sheet lamination	
Refraction content:	64-68%	
Viscosity	700~2500 mPa.s	Brookfield LVT/ 3# / 30 rpm / 60°C
pH	~6.0	
<u>Character</u>	White milky jelly	
Application control		
Temperature	55 ~ 65°C	
Cleaning	Not dried glue can easily be removed with cold water. Dried glue can be removed with warm water	
Waste disposal	Refer to safety data sheet.	
<u>Safety reference</u>	The safety data sheet is applicable.	
<u>Storage</u>	6 months in closed package at 15 ~ 25°C	

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.

Henkel Technologies — Domestic contact
Beijing: 010-8453 8899 Shanghai: 021-2891 8000
Guangzhou: 020-8207 5875 HongKong: 852-2233 0000
industrial-adhesives@henkel.com . www.industrial-adhesives.com



Technologies
Industrial Adhesives